

TONY®

曲臂縫紉機 · 不附拉輪


FEED OFF THE ARM MACHINE WITHOUT PULLER




✓ H-927-M

2 NEEDLES FEED OFF THE ARM DOUBLE CHAIN STITCH MACHINE.


雙針包縫機



2 NEEDLE
二針



3 NEEDLE
三針



Machine head	Needle gauge (mm)	Materials
Twin needles	3.2(1/8), 4.8(3/16), 6.4(1/4)	Thin, Medium
Twin needles	4.8(3/16), 6.4(1/4)	Heavy
Three needles	6.4(1/8x2)	Thin, Medium, Heavy, Extra Heavy

Needle: TV x 5 #19-#21 (Heavy materials 厚料)

TV x 64 #11-#16 (Thin / Mid materials 薄料 / 中料)



✓ H-928-H

3 NEEDLES FEED OFF THE ARM DOUBLE CHAIN STITCH MACHINE.

三針包縫機

APPLICATIONS / 用途:









Men Suit and Ladies Dress, Shirts, Blouses, Sports Shirts, Pajamas, Work Suits, Denim Jackets, Jeans.
男裝、女裝、襯衫、工作服、運動服、牛仔褲。



針距可以自由調整，只要在轉動皮帶輪的同時按下針距調整鈕，讓按鈕卡進機身內針距組之凹洞即可調整。

The stitch length can be changed simply by pressing a button while turning the machine pulley to align the scale marks.

SPECIFICATIONS:

MODEL	 Double chain stitch	 No. of needle	 Max. stitch length (m/m)	 Thin materials	 Medium materials	 Heavy materials	 Height of presser foot (m/m)	 Max. sewing speed (rpm)
H-927	★	2	3.0~4.2	★	★	★	10	4,000
H-928	★	3	3.0~4.2	★	★	★	11	4,000