

六本木
ROPPONGI

专注 | 专业 | 极致
FOCUS | PROFESSIONAL | ULTIMATE

RO-V100Series
全自动袋口机
Automatic bag mouth machine



■ 引进技术

THE IMPORTED TECHNOLOGY

- 转盘式收料装置(可储存900个袋口)
- 步进马达驱动特制传送带
- 可调节式拉盘
- 可调节式机身
- 自动拉筒转换器便捷
- 日本原装传感器
- 可升降机架
- Turntable-type receiving device can store 900 bag mouths
- Special conveyor belt driven by step motor
- Adjustable pull drum
- Adjustable body
- Automatic cylinder switch is simple and convenient
- Japanese original sensor
- Can lift frame

机头: 双针链缝/单针平缝相比国际广机头	Double Needle Chain / Single Needle Lockstitch With Original Machine Head
最高转速: 4200rpm	Maximum speed 4200 rpm
车缝长度: 0.9 mm - 5 mm	Sewing length: 0.9 mm - 5 mm
标准针距: 1/4" (5.4 mm)	Standard needle pitch: 1/4" (5.4 mm)
可缝料厚: 1/32" (1.2 mm) / 1/8" (3.6 mm) / 1/4" (11.7 mm)	Optional needle pitch: 1/32" (1.2 mm) / 1/8" (3.6 mm) / 1/4" (11.7 mm)
机头: DPX17-438	Model: dpx17-438
最高产量: 2000 个/时	Maximum output: 2000 pieces/hour
电压: 220V 50 / 60Hz	Voltage: 220 V 50 / 60Hz



■ 机架升降功能

RACK LIFT FUNCTION

机器特点:

六本木V100无需调整机器便可车缝不同的布料(各种厚薄布料, 材质从尼龙到厚的牛仔布料), 各种不同尺寸的袋口上所展现的灵活性可以和它在高生产效率上的优势相媲美; 袋口车缝效果极佳。

*创新的气动传输系统配备了一条可以根据口袋材料和形状自我调整的皮带以及配备了适合不同缝边样式的可调节拉筒, 卷边口不会有拉长或弯曲的问题。

*全球首创全自动拉筒(专利产品)可自由选择2分、3分、4分、散口环口等车缝。

*可拉出式机头, 方便了更好的穿线空间, 解决了穿线难的问题。

*进料收料, 自动打开, 进入面料和收料都很顺畅。

*采用了升降式机架, 可按操作人员的身高自由调整机器高度。

*转盘式收料装置, 多段式, 更直观收料。

*双针链式, 或锁式线迹, (3800锁式双针, 飞马撞破机, 关西机头, 可选配)。

*沟槽式传输带, 保证了皮带不跑偏。

专注 | 专业 | 极致
FOCUS | PROFESSIONAL | ULTIMATE

Machine Features

The ROPPONGI V100 can sew a variety of fabrics (thick and thin, from nylon to thick denim) without the need to adjust the machine. The flexibility exhibited by the pocket opening of the size is comparable to its advantages in high production efficiency, the pocket opening is very well sewn.

* The innovative pneumatic transmission system is equipped with a belt that adjusts itself to the pocket material and shape and is equipped with different seam patterns. The adjustable pull cylinder, the curling mouth will not have the problem of stretching or bending.

* The world's first fully automatic pulling drum (patented product) can freely choose 2 points, 3 points, 4 points, loose openings, ring openings, etc.

* The pull-out machine head facilitates a better threading space and solves the problem of difficult threading.

* Feeding and receiving, automatically opening, entering the fabric and receiving the material smoothly.

* The lift frame is adopted, and the height of the machine can be adjusted freely according to the height of the operator.

* Turntable type receiving device, multi-stage type, more intuitive material receiving.

* Double needle chain, or lockstitch, (3800 double lock, Pegasus interlock, Kansai head, optional)

* Grooved conveyor belt ensures that the belt does not deviate.

