


单线点缝暗缝机

Single thread Blindstitch spot tacking machine














单线点缝暗缝机

这点缝机可用于男女装外衣上的多种工序：在裤脚反起部份以及裤腰反起的边缘为标签点结。非常牢固的点套结不会在衣服外留下痕迹，备有标签点套结或夹克门襟点套结车缝装置可供选配。

Single thread Blindstitch spot tacking machine

This spot tacking machine is used for several operations in the ladies' and men's outer wear industry: Woven labels can be tacked as well as turned-under hems or edges and turned-up trouser bottoms. It's durable blind spot tacks do not leave any marks on the outside of the garment. Due to optional equipment this machine can get converted to manufacture leather labels or to tack lapel points of jackets.



	速度 / Speed 机器最高缝速 / mechanically admissible 建议车缝速度 / Recommended rated speed	1800 min-1 1600 min-1
	点缝长度 / stitches per tack	6 - 14
	针板开口 / needle plate opening	8,0 mm 4,5 mm / 选配件 / optional 6,0 mm / 选配件 / optional 10,0 mm / 选配件 / optional
	松弛线步 / loose seam	
 digital	数字式缝线深度调节 / stitch depth display digital	选配件 / optional
	机针摆动 / needle oscilation	
	二个针线张力器 / 2 thread tensions	
	机针型号 / needle system 机针号数 / needle size	Strobel 1717 90 - 110
	圆形工作台 / round workplate	选配件 / optional 直径 / diameter 26 mm / 80 mm / 旋转 / revolving 130 mm
	可拆式工作台 / removeable work plate	选配件 / optional
	剪线装置 / thread trimmer	

针数 / number of stitches	6, 8, 10, 12, 14
电机功率 / min. motor power	370 W
同步齿轮 / toothed belt pulley/machine	Z = 38
同步皮带 / toothed belt profile	HTD 5M-9
针步类型 / stitch type	单线点缝线步 / single thread blind stitch spot tacking
建议缝线 / recommended thread	PES No 120 - 300
空气压力 / pneumatic connection	6 bar
平均空气用量 / avarage air consumption	110/h
需要空间 / required space	0,6 m x 1,06 m
工作噪音 / operating noise at 2200 min-1 nach DIN 45635-48-1 KL3	LpAm 71 dB(A)